


E-70

Back



Performance and Component Data

- E-70** Use with commercial R-22 40 through 60 ton refrigerant circuit.
Or with R-134A 25 through 40 ton refrigerant circuit.
- Heat Exchanger Coil**
Tube in Tube Exchanger
Outside hot gas tube Steel Tested @ 450 PSI
Inside tube Double Walled vented copper. UL Listed for potable water.
Double wall with vent between walls isolates water from refrigerant. Tested 450 PSI
Three coils parallel in balanced manifold to ensure proper refrigerant flow.
- Water Circulation Pump**
Grundfos or Taco -- Stainless Steel - 1/12 H.P.
Single Phase - 208/230 volts - 60 HZ - .80 amps.
Water Lubricated - Needs no oiling - Overload Protected - UL Listed
- Pump on/off Control**
Head Pressure Control - Adjustable with 30 PSI differential
Set @ 200 PSI for R-22 & @ 130 PSI for R-134A
Manufactured by Alco.
- Pump Speed Control**
Variable speed control to regulate RPM of circulating pump in reference to head pressure. Manufactured by Alco.
- 6. Tubing Connections — Copper —**
Refrigerant 2 1/8" OD ---- Water 1 3/8" OD
- 7. Dimensions — 17" X 26" X 46" Weight — 215 Lbs.**
- 8. Performance Ratings — 70° F rise. I.e. 70° F to 140° F with constant circulation in tank**

R-22 Air Cooled		R-134A Water Cooled	
40 ton	217,700 BTU/Hr.	25 ton	95,200 BTU/Hr.
50 ton	272,000 BTU/Hr.	30 ton	114,200 BTU/Hr.
60 ton	326,600 BTU/Hr.	40 ton	152,300 BTU/Hr.

Note: In View of Continuous Product Improvements—design and specification are subject to change without Notice

Heat Harvester Energy Efficient Products
Manufactured by
Environmentally Engineered Equipment, Inc.