



Compressor	HP	20				30				40				50			
		208-230 V		460 V		208-230 V		460 V		208-230 V		460 V		208-230 V		460 V	
Voltage	V/3/60Hz	410A	134a	410A	134a	410A	134a	410A	134a	410A	134a	410A	134a	410A	134a	410A	134a
Refrigerant																	
RLA	Amps	47.9	33.2	20.7	14.9	55.7	43.5	26.0	22.3	75	60.0	36.4	27.8	94.3	71.5	46.4	39.6
LRA	Amps	267	265	130	120	320	420	160	175	485	460	215	215	560	560	260	220
MCA	Amps	107.8	74.7	46.6	33.5	125.3	97.9	58.5	50.2	168.8	135.0	81.9	62.6	212.2	160.9	104.4	89.1
MOCP	Amps	119.8	83.0	51.8	37.3	139.3	108.8	65.0	55.8	187.5	150.0	91.0	69.5	235.8	178.8	116.0	99.0
Dry Weight	lbs	1170				1320				1690				1820			

Note: In View of Continuous Product Improvements, design and specification are subject to change without notice. EEE can accept no responsibility for possible errors in catalogues, brochures and other printed material.



Customer: _____
 Project: _____
 Sales Rep: _____
 Date: AUGUST 2008 Brochure No 801
 COPYRIGHT 2008 EEE, INC. ALL RIGHTS RESERVED.

ENVIRONMENTALLY ENGINEERED EQUIPMENT, INC

SERIES: DS 20/30/40/50

Water-to-Water Heat Pumps